

TECHNICAL DATA SHEET

CABLE DRUM COMPONENTS – S1S2E



The mark of
responsible forestry



1. Species

Pinus Taeda / Pinus Radiata

Moisture Content:

KD 10–12% ($\pm 2\%$)

2. Description:

Kiln-dried pine lumber, planed on one face and squared on two edges (S1S2E), intended for the manufacturing of cable drums. The product is designed for industrial applications requiring good structural strength, dimensional stability, and proper performance in machining and assembly processes. Edge radius is produced according to customer specifications.

Profile:

As per customer requirements.

Accepts:

- Sound and tight knots.
- Pith allowed provided it is solid and stable.
- Minor defects that do not affect the structural strength of the piece.

Does not accept:

- Undersize
- Any defect that affects the structural stability or strength of the piece.

End Trim:

Precise 90° cut.

Dimensional tolerance:

Thickness and width : $\pm 0,3\text{mm}$ / $\pm 2\text{ mm}$

Length : $\pm 0/-2\text{mm}$





www.asun.cl

Prestigious clients in Japan, Korea, Taiwan, Thailand, China, Malaysia, Europe, the Middle East, the USA, Canada, Mexico and Central America.

ASUN Chile Ltda. Headquarters
Avenida Prat 199, Torre A OF 1009 | Concepción - Chile - C.P. 4030000
Phone: (56) 41 - 2127780 mail: contacto@asun.cl



@aserraderos_unidos_asun

